I-QWIK PROX SERIES

PROX STAND ALONE ACCESS CONTROL

MARKS #		LOCKSET TYPE - PACKED PER CASE	# OF USERS	AUDIT TRAIL EVENTS	FINISH GROUPS	
IQ1PROX	IQ1P/26D				19 Black Powder Coat; 26D American Levers	26D Satin Chrome
		IQ1: Cylindrical Lockset - *PACKED 4 PER CASE* **For i-Qwik/i-Que Options & Accessories, See Pages 26-27**	3008	1180	**725**	**795**
IQ2PROX	IQ2P/26D					
		IQ2: Mortise Lockset - *PACKED 4 PER CASE* **For i-Qwik/i-Que Options & Accessories, See Pages 26-27**	3008	1180	**1000**	**1070**
IQ7PROX	IQ7P/26D					
		IQ7: Rim Exit Device Interface - *PACKED 6 PER CASE* *Adapter plates operate most manufacturers Rim Exit Devices. Adapter plates for Mounting Exit Devices are sold separately, see page 27.* **For i-Qwik/i-Que Options & Accessories, See Pages 26-27**	3008	1180	**905**	**975**

Standard Features

- ***CableGard™*** protects wires for easy installation
- Weatherproof standard
- Shielded electronics
- 16 Digit tactile metal keypad
- 3008 User capability
- 1180 Event audit trail (*Audit trail requires i-Dat module, see page 30)*
- 1600 Scheduled events
- 56 Programmable holidays
- Real time clock
- Multiple entry codes for max security
- Full scheduling features
- Pin only
- Terminator on/off
- Built in relay
- 3-10 Digit user code
- Temporary user codes
- First manager to arrive
- Panic alarm interface
- Two wire remote release
- Fire tower lock function
- Accepts HID cards and fobs in 26, 33 and 37 format
- Programmable by keypad or by use of the i-Dat software package *(i-Dat package sold separately, see page 30 for more information)*
- Privacy mode *(input to lockout keypad entry)*
- Scheduled/Manual passage mode
- Audible & visible entry indicator
- Audible low battery alert
- 4 "AA" batteries included
- **HI-SECURITY™ Cylinder Standard (Cylindrical Model Only)**
- Lifetime Mechanical Warranty; 2 Year Electronic Warranty
- ***Additional Finishes, Consult Factory***

IQ1 PROX Cylindrical Lockset Specifications

Door Thickness: 1-3/4" standard
Spacer kit available for thinner doors; For thicker doors consult factory.
Handing: Non-handed
Key Override: Marks HI-SECURITY™ Cylinder std. Marks "C" Keyway, 6 pin w/2 keys, IC Core optional
Lock Body: Grade 2 Cylindrical "Survivor"
Latch: Grade 2, 2-3/4" backset, reversible with 9/16" throw, 3 Hr UL fire rating
Clutch: The "Clutch" for trouble free service
Strike Plate: 4-7/8" ASA strike

IQ2 PROX Mortise Lockset Specifications

Door Thickness: 1-3/4" standard
Spacer kit available for thinner doors; For thicker doors consult factory.
Handing: Field reversible
Key Override: 1-1/8" Mortise cylinder, Marks "C" Keyway, 6 pin w/2 keys, or 1-3/8" IC Core housing optional
Lock Body: Grade 1, Series 5, 2-3/4" backset, 3/4" anti-friction latch, 3 Hr UL fire rating
Auxiliary Latch: 1/2" throw
Bolt Throw: 1" *(Optional deadbolt functions - Consult factory)*
Hubs: Steel, 5/16" square with security separator
Clutch: The "Clutch" for trouble free service
Strike Plate: 4-7/8" ASA standard

IQ7 PROX Rim Exit Device Interface Specifications

Door Thickness: 1-3/4" - 2-1/4" standard
Spacer kit available for thinner doors; For thicker doors consult factory.
Handing: Non-handed
Key Override: 1-1/8" Mortise cylinder, Marks "C" Keyway, 6 pin w/2 keys, or 1-3/8" IC Core housing optional
Clutch: The "Clutch" for trouble free service

Adapter plates operate most manufacturers Rim Exit Devices. Adapter plates for Mounting Exit Devices are sold separately, see page 27.

How To Order Example for i-Qwik PROX Series Electronic Access Control Locksets

IQ	7PROX	—	F22
1. Lockset Series	*2. Model Number*	*Dash*	*4. Options*

❒ **IQ**

❒ **1PROX (Cylindrical)** ❒ **1P/26D (Cylindrical)**
❒ **2PROX (Mortise)** ❒ **2P/26D (Mortise)**
❒ **7PROX (Rim Exit Device Interface)** ❒ **7P/26D (Rim Exit Device Interface)**

OPTIONS

_____

Access Control

FOR ADDITIONAL DESIGNS, ASK FOR THE CUSTOM LOCK DIVISION CATALOG OR VISIT OUR WEBSITE @ WWW.MARKSUSA.COM
631-225-5400 • 1-800-526-0233 • Fax 631-225-6136 • ©2009 MARKS USA